

硬质合金系列——削平柄钢板钻

T.C.T Annular cutter with Weldon shank

削平柄 柄径 $\Phi 19.05\text{mm}$ 适用于两颗螺钉紧固定位装夹的接口。主要适用于 Hougen, Jancy, Nitto, Alfra, BDS, Ruko, Rotabroach 等各种磁座钻机。

T.C.T Annular cutter with Weldon shank, the diameter of shank is $\Phi 19.05\text{mm}$, which is suitable for two-point perpendicular positioning loading and unloading. Weldon shank, suitable for all types of magnetic drills like Hougen, Jancy, Nitto, Alfra, BDS, Ruko, Rotabroach...

钻孔直径 Cutting Dia(mm)	钻孔深度 Cutting Depth(mm)
12-150mm	35mm
12-150mm	55mm
18-135mm	75mm



硬质合金系列——快换柄钢板钻

T.C.T Annular cutter with one-touch shank

硬质合金快换柄系列 柄径 $\Phi 19.05\text{mm}$, 三点定位快速装卸夹头也可用螺钉紧固定位装夹的接口。主要适用

Hougen,Jancy,Nitto,Alfra,BDS,Ruko,Rot abroad 等各种磁座钻机。

T.C.T annular cutter with one-touch shank, the diameter of shank is $\Phi 19.05\text{mm}$, which is suitable for Quick-change arbor connector with 120° three-point positioning and arbor connector with 90° two-point perpendicular positioning. One-touch shank, suitable for all types of magnetic drills like Hougen,Jancy,Nitto,Alfra,BDS,Ruko,Rota broach...



硬质合金系列——四孔柄系列

T.C.T Annular cutter with FEIN Quick-in shank

四孔柄 柄径 $\Phi 18.0\text{mm}$, 特征在于 90° 度分布 4 点定位孔。适用于 FEIN 系列磁座钻机。

T.C.T annular cutter with FEIN Quick-in Shank, the diameter of shank is $\Phi 18.0\text{mm}$, which is suitable for 90° distribution at 4 locating holes. FEIN Quick-in Shank, suitable for FEIN magnetic drills.



钻孔直径 (mm)Cutting Dia	钻孔深度 (mm)Cutting Depth
12-65mm	35mm
12-65mm	55mm

硬质合金系列——螺纹柄钢板钻

T.C.T Annular cutter with thread shank

螺纹柄 内螺纹 M18*6P1.5, 适用于 FEIN/HITACHI 等的螺纹接口磁座钻机。

T.C.T annular cutter with thread shank, cutter range with M18*6P1.5 thread. It is suitable for FEIN/HITACHI magnetic drills.



钻孔直径 (mm)Cutting Dia	钻孔深度 (mm)Cutting Depth
12-50mm	55mm